

A large, bold, black letter 'S' is positioned on the left side of the page. It is partially enclosed by a gray rectangular block that is tilted slightly to the right. A horizontal line extends from the left edge of this gray block across the top of the page.

SAFETY DATA SHEET

Nickel Metal Hydride Battery 6182062

Number 6897267-R1

**cascade[®]
corporation**

2201 NE 201st. Ave.
Fairview, OR 97024-9718
1-800-227-2233
www.cascorp.com

Cascade is a Registered Trademark of Cascade Corporation

Model: Nickel Metal Hydride Battery – Rechargeable
Number: 6182062

Prepared by	Approved by
Steve Wittkop	Greg Nagle
Date: September 4, 2017	Date: September 4, 2017

1. PRODUCT AND COMPANY IDENTIFICATION

PRODUCT IDENTIFICATION

Nickel Metal Hydride Battery

Nominal Voltage : 1.2 V per cell – Rechargeable

MANUFACTURER

Cascade Corporation
2201 NE 201st Ave, Fairview, Oregon 97024
Contact person: Greg Nagle
Telephone: 1-800-227-2233
Fax: 503-669-6701
E-mail: greg.nagle@cascorp.com

2. HAZARDS IDENTIFICATION

- Ingestion: Swallowing a battery can be harmful. Contents of an open battery can cause serious chemical burns of mouth, esophagus, and gastrointestinal tract.
- Inhalation: Contents of an open battery can cause respiratory irritation. Hypersensitivity to nickel can cause allergic pulmonary asthma.
- Skin Contact: Contents of an open battery can cause skin irritation and/or chemical burns. Nickel, nickel compounds, cobalt and cobalt compounds can cause skin sensitization and an allergic contact dermatitis.
- Eye Contact: Contents of an open battery can cause severe irritation and chemical burns.
- Note: Nickel, nickel compounds, cobalt and cobalt compounds are listed as possible carcinogens by the International Agency for Research on Cancer (IARC) or National Toxicology Program (NTP).

3. INGREDIENTS

IMPORTANT: The battery should not be opened or burned. Exposure to the ingredients contained within or their combustion products could be harmful.

MATERIAL OR INGREDIENT	PEL (OSHA)	TLV (ACGIH)	%/wt.
Aluminum (CAS# 7429-90-5)	15 mg/m3 TWA (total dust) 5 mg/m3 TWA (respirable fraction)	10 mg/m3 TWA	< 2.0
Cobalt as cobalt metal (CAS# 7440-48-4) as cobalt oxide (CAS# 1307-96-6) as cobalt hydroxide (CAS# 21041-93-0)	0.1 mg/m3 TWA (as Co)	0.02 mg/m3 TWA (as Co)	2.5-6.0
Lithium Hydroxide (CAS# 1310-65-2)	None established	None established	0-4.0
Manganese (CAS# 7439-96-5)	5 mg/m3 Ceiling	0.2 mg/m3 TWA (as Mn)	< 3.0
Mischmetal including: Lanthanum (CAS# 7439-91-0) Cerium (CAS# 7440-45-1) Neodymium (CAS# 7440-00-8) Praseodymium (CAS# 7440-10-0)	15 mg/m3 TWA (particulates not otherwise regulated- total dust) 5 mg/m3 TWA (particulates not otherwise regulated- respirable fraction)	10 mg/m3 TWA (particulates not Oth- erwise classified-inhal- able) 3 mg/m3 TWA (particulates not otherwise classified- respirable)	< 13.0
Nickel as nickel hydroxide (CAS# 12054-48-7) as nickel oxide (CAS# 1313-99-1) as nickel powder (CAS# 7440-02-0)	1 mg/m3 TWA (as Ni)	1.5 mg/m3 TWA (as inhalable Ni) 0.2 mg/m3 TWA (as inhalable Ni, insoluble compounds)	30-50
Potassium Hydroxide (CAS# 1310-58-3)	None established	2 mg/m3 Ceiling	< 7.0
Sodium Hydroxide (CAS# 1310-73-2)	2 mg/m3 TWA	2 mg/m3 Ceiling	0-4.0
Zinc as zinc metal (CAS# 7440-66-6) as zinc oxide (CAS# 1314-13-2) as zinc hydroxide (CAS# 20427-58-1)	15 mg/m3 TWA (total dust: zinc oxide) 5 mg/m3 TWA (respirable fraction: zinc oxide)	10 mg/m3 TWA (total dust: zinc oxide)	< 3.0
Non-Hazardous Components Steel (iron CAS# 7439-89-6) Water, Paper, Plastic and Other	None established None established	None established None established	14-18 Balance

4. FIRST AID MEASURES

Ingestion:	Do not induce vomiting or give food or drink. Seek medical attention immediately
Inhalation:	Provide fresh air and seek medical attention.
Skin Contact:	Remove contaminated clothing and wash skin with soap and water. If a chemical burn occurs or if irritation persists, seek medical attention.
Eye Contact:	Immediately flush eyes thoroughly with water for at least 15 minutes, lifting upper and lower lids, until no evidence of the chemical remains. Seek medical attention.

5. FIRE FIGHTING MEASURES

If fire or explosion occurs when batteries are on charge, shut off power to charger.

In case of fire where nickel metal hydride batteries are present, apply a smothering agent such as sand, dry ground dolomite, or soda ash, or flood the area with water. A smothering agent will extinguish burning nickel metal hydride batteries. Water may not extinguish burning batteries but will cool the adjacent batteries and control the spread of fire. Burning batteries will burn themselves out. Virtually all fires involving nickel metal hydride batteries can be controlled with water. When water is used, however, hydrogen gas may evolve. In a confined space, hydrogen gas can form an explosive mixture. In this situation, smothering agents are recommended.

Fire fighters should wear self-contained breathing apparatus. Burning nickel metal hydride batteries can produce toxic fumes including oxides of nickel, cobalt, aluminum, manganese, lanthanum, cerium, neodymium, and praseodymium.

6. ACCIDENTAL RELEASE MEASURES

To cleanup leaking batteries:

Ventilation Requirements:	Room ventilation may be required in areas where there are open or leaking batteries.
Eye Protection:	Wear safety glasses with side shields if handling an open or leaking battery.
Gloves:	Use neoprene or natural rubber gloves if handling an open or leaking battery. Battery materials should be collected in a leak-proof container.

7. HANDLING AND STORAGE

Storage:	Store in a cool, well ventilated area. Elevated temperatures can result in shortened battery life.
Mechanical Containment:	<p>If potting or sealing the battery in an airtight or watertight container is required, consult Cascade Corporation for precautionary suggestions. Batteries normally evolve hydrogen which, when combined with oxygen from the air, can produce a combustible or explosive mixture unless vented. If such a mixture is present, short circuits, high temperature, or static sparks can cause an ignition.</p> <p>Do not obstruct safety release vents on batteries. Encapsulation (potting) of batteries will not allow cell venting and can cause high pressure rupture.</p>
Handling:	<p>Accidental short circuit for a few seconds will not seriously affect the battery. Prolonged short circuit will cause the battery to lose energy, and can cause the safety release vent to open. Sources of short circuits include jumbled batteries in bulk containers, metal jewelry, metal covered tables or metal belts used for assembly of batteries into devices. If soldering or welding to the battery is required, consult Cascade Corporation for proper precautions to prevent seal damage or short circuit. Do not open battery. The negative electrode material may be pyrophoric. Should an individual cell from a battery become disassembled, spontaneous combustion of the negative electrode is possible. This is much more likely to happen if the electrode is removed from its metal container. There can be a delay between exposure to air and spontaneous combustion.</p>

7. HANDLING AND STORAGE (CONTINUED)

Charging: This battery is made to be charged many times. Because it gradually loses its charge over a few months, it is good practice to charge battery before use. Use recommended charger. Improper charging can cause heat damage or even high pressure rupture. Observe proper charging polarity.

Labeling: If the label or package warnings are not visible, it is important to provide a package and/or device label stating:

WARNING: CHARGE ONLY WITH SPECIFIED CHARGERS ACCORDING TO DEVICE MANUFACTURER'S INSTRUCTIONS. DO NOT OPEN BATTERY, DISPOSE OF IN FIRE OR SHORT CIRCUIT - MAY IGNITE, EXPLODE, LEAK OR GET HOT CAUSING PERSONAL INJURY.

8. EXPOSURE CONTROL/PERSONAL PROTECTION

Ventilation Requirements: Not necessary under normal conditions.

Respiratory Protection: Not necessary under normal conditions.

Eye Protection: Not necessary under normal conditions.

Gloves: Not necessary under normal conditions.

9. PHYSICAL AND CHEMICAL PROPERTIES

Boiling Point @ 760 mm Hg (°C)	Not applicable for an Article
Vapor Pressure (mm Hg @ 25°C)	Not applicable for an Article
Vapor Density (Air = 1)	Not applicable for an Article
Density (g/cm ³)	2.2 - 3.7
Percent Volatile by Volume (%)	Not applicable for an Article
Evaporation Rate (Butyl Acetate = 1)	Not applicable for an Article
Physical State	Solid
Solubility in Water (% by weight)	Not applicable for an Article
pH	Not applicable for an Article

10. STABILITY AND REACTIVITY

Nickel metal hydride batteries do not meet any of the criteria established in 40 CFR 261.2 for reactivity.

11. TOXICOLOGICAL INFORMATION

Nickel metal hydride batteries are not hazardous waste. Under normal conditions of use, nickel metal hydride batteries are non-toxic.

12. ECOLOGICAL INFORMATION

Issues such as ecotoxicity, persistence and bioaccumulation are not applicable for articles.

13. DISPOSAL CONSIDERATIONS

Dispose of in accordance with all applicable federal, state and local regulations. Appropriate disposal technologies include incineration and land filling. Nickel metal hydride batteries can also be collected as part of the Rechargeable Battery Recycling Corporation (RBRC) program.

14. TRANSPORT INFORMATION

In general, all batteries in all forms of transportation (ground, air, or ocean) must be packaged in a safe and responsible manner.

Regulatory concerns from all agencies for safe packaging require that batteries be packaged in a manner that prevents short circuits and be contained in "strong outer packaging" that prevents spillage of contents. All original packaging for nickel metal hydride batteries has been designed to be compliant with these regulatory concerns.

Nickel metal hydride batteries (sometimes referred to as "Dry cell" batteries) are not defined as dangerous goods under the IATA Dangerous Goods Regulations, ICAO Technical Instructions and the U.S. hazardous materials regulations (49 CFR).

Nickel metal hydride batteries are defined as dangerous goods under the IMDG code.

For air and ground transportation, these batteries are not subject to the dangerous goods regulations as they are compliant with the requirements contained in the following special provisions.

Regulatory Body	Special Provisions
ADR	295 - 304, 598
IMDG	UN3496 SP 963
UN	UN 3028 Provisions 295 - 304
US DOT	49 CFR 172.102 Provision 130
IATA	A123
ICAO	UN 3028 Provisions 295 - 304

In addition, the IATA Dangerous Goods Regulations and ICAO Technical Instructions require the words "not restricted" and the Special Provision number A123 be provided on the air waybill, when an air waybill is issued.

15. REGULATORY INFORMATION

Batteries marketed by Cascade Corporation are not classified as dangerous goods by the major international regulatory bodies and are therefore not regulated.

SARA/TITLE III - As an article, this battery and its contents are not subject to the requirements of the Emergency Planning and Community Right-To-Know Act.

16. OTHER INFORMATION

None

Do you have questions you need answered right now?

Call your nearest Cascade Service Department.

Visit us online at www.cascorp.com

AMERICAS

Cascade Corporation

U.S. Headquarters

2201 NE 201st

Fairview, OR 97024-9718

Tel: 800-CASCADE (227-2233)

Fax: 888-329-8207

Cascade Canada Inc.

5570 Timberlea Blvd.

Mississauga, Ontario

Canada L4W-4M6

Tel: 905-629-7777

Fax: 905-629-7785

Cascade do Brasil

Praça Salvador Rosa,

131/141-Jordanópolis,

São Bernardo do Campo - SP

CEP 09891-430

Tel: 55-13-2105-8800

Fax: 55-13-2105-8899

EUROPE-AFRICA

Cascade Italia S.R.L.

European Headquarters

Via Dell'Artigianato 1

37030 Vago di Lavagno (VR)

Italy

Tel: 39-045-8989111

Fax: 39-045-8989160

Cascade (Africa) Pty. Ltd.

PO Box 625, Isando 1600

60A Steel Road

Sparton, Kempton Park

South Africa

Tel: 27-11-975-9240

Fax: 27-11-394-1147

ASIA-PACIFIC

Cascade Japan Ltd.

2-23, 2-Chome,

Kukuchi Nishimachi

Amagasaki, Hyogo

Japan, 661-0978

Tel: 81-6-6420-9771

Fax: 81-6-6420-9777

Cascade Korea

121B 9L Namdong Ind.

Complex, 691-8 Gojan-Dong

Namdong-Ku

Inchon, Korea

Tel: +82-32-821-2051

Fax: +82-32-821-2055

Cascade-Xiamen

No. 668 Yangguang Rd.

Xinyang Industrial Zone

Haicang, Xiamen City

Fujian Province

P.R. China 361026

Tel: 86-592-651-2500

Fax: 86-592-651-2571

Cascade India Material

Handling P Ltd

Sy no 271/8, Ingawale Patil

Estate,

Godown No.9,10 & 11, Bhugaon,

Off Paud Road, Tal Mulshi, Dist

Pune 411 042

Cascade Australia Pty. Ltd.

1445 Ipswich Road

Rocklea, QLD 4107

Australia

Tel: 1-800-227-223

Fax: +61 7 3373-7333

Cascade New Zealand

15 Ra Ora Drive

East Tamaki, Auckland

New Zealand

Tel: +64-9-273-9136

Fax: +64-9-273-9137

Sunstream Industries

Pte. Ltd.

18 Tuas South Street 5

Singapore 637796

Tel: +65-6795-7555

Fax: +65-6863-1368

